



# RODACO R1

Great tire  
for low intensity applications,  
produced in advanced tire  
manufacturing facility

## 2 LAYER NATURAL RUBBER CONSTRUCTION

- Maximizes stability
- Steel beads prevent rim slip

## WIDE AND DEEP LUG PATTERN

- Maximizes traction
- Maximizes braking performance



# SIZE AVAILABILITY LIST



PART NO	DESCRIPTION	TIRE SIZE	BRAND/ PRODUCT NAME	TREAD PATTERN	ACTUAL TIRE DIMENSION		LOAD CAPACITY [kg]					
							COUNTERBALANCED LIFT TRUCKS		OTHER VEHICLES			STATIC
					OVERAL DIAMETER [mm]	OVERAL WIDT [mm]	LOAD WHEEL upto 25km/h	STEERING WHEEL upto 25km/h	UP TO 10 km/h	UP TO 16 km/h	UP TO 25 km/h	0 km/h
9.315.15273	5.00 - 8 / 3.00 AT RODACO R1	5.00 - 8	RODACO R1	AT	451	122	1415	1090	1415	1285	1090	1645
9.359.15279	18 X 7 - 8 / 4.33 AT RODACO R1	18 X 7 - 8	RODACO R1	AT	449	150	2145	1650	2145	1945	1650	2490
9.337.15275	6.00 - 9 / 4.00 AT RODACO R1	6.00 - 9	RODACO R1	AT	517	138	1885	1450	1885	1710	1450	2190
9.7.15253	6.50 - 10 / 5.00 AT RODACO R1	6.50 - 10	RODACO R1	AT	564	162	2340	1800	2340	2125	1800	2720
9.33.15255	7.00 - 12 / 5.00 AT RODACO R1	7.00 - 12	RODACO R1	AT	652	165	2920	2240	2920	2645	2240	3380
9.49.15259	7.00 - 15 / 5.50 AT RODACO R1	7.00 - 15	RODACO R1	AT	725	179	3545	2725	3545	3215	2725	4115
9.77.15261	8.25 - 15 / 6.50 AT RODACO R1	8.25 - 15	RODACO R1	AT	816	217	4615	3550	4615	4190	3550	5360
9.1403.15389	250 - 15 / 7.00 AT RODACO R1	250 - 15	RODACO R1	AT	709	233	4745	3650	4745	4310	3650	5510
9.200.15267	28 X 9 - 15 / 7.00 AT RODACO R1	28 X 9 - 15	RODACO R1	AT	688	218	3770	2900	3770	3420	2900	4380
9.237.15269	300 - 15 / 8.00 AT RODACO R1	300 - 15	RODACO R1	AT	807	265	5850	4500	5850	5310	4500	6795

\*Sve ostale dimenzije po upitu.

