

MINING & EARTHMOVER

MAGNA MA08 L4/L5

The Magna MA08 is designed for use on wheel loaders, dozers and graders requiring maximum traction.

The optimized square-shouldered design provides stability and protection from cuts.



The aggressive L5 open tread pattern provides grip and traction.



All steel radial construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	Load symbol	Tra code	Max. speed (km/h)	Load/speed index	Single max. load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Tyre weight (kg)
20.5R25	MA08	**	L5	10	193A2	11500 kg/6.5 bar	17.00/2.0	1548	521	72	365
23.5R25	MA08	**	L5	10	201A2	14500 kg/6.5 bar	19.50/2.5	1673	597	78	475
26.5R25	MA08	**	L5	10	209A2	18500 kg/6.5 bar	22.00/3.0	1800	673	87	632
29.5R25	MA08	**	L5	10	216A2	22400 kg/6.5 bar	25.00/3.5	1921	750	95	866
29.5R29	MA08	**	L5	10	218A2	23600 kg/6.5 bar	25.00/3.5	2023	750	95	889
35/65R33	MA08	**	L4	10	224A2	28000 kg/6.5 bar	28.00/3.5	2075	880	63	919
35/65R33	MA08	**	L5	10	224A2	28000 kg/6.5 bar	28.00/3.5	2075	880	97	1079