

CAMSO DMP 532



MINI-DUMPERS



ROADING COMFORT AND OFF-ROAD TRACTION

A versatile mini-dumper tire solution providing great off-road traction while reducing vibrations for better driving comfort from site to site.

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO DMP 532



WIDE LUG SPACING

- Creates great self-cleaning behaviour

CENTRE REINFORCEMENT BAR AND INCREASED CENTRE LUG VOLUME

- Increases comfort and stability on harder surfaces



LOW ASPECT TIRE SIZE

- Maximizes traction, flotation and stability

WIDE AND AGGRESSIVELY CURVED TREAD

- Provides excellent off-road traction and stable ground contact

TIRE SIZE	RIM SIZE Recommended (permitted)	ACTUAL TIRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	SERVICE	INFLATION PRESSURE [bar] [PSI]	MAXIMUM TIRE LOAD [kg] [lb]						
		O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32nd]	S.L.R. [mm] [in]	R.C. [mm] [in]					Static	10 km/h 6 mph	25 km/h 16 mph	30 km/h 19 mph	35 km/h 22 mph	50 km/h 31 mph	
500/60-22.5 IMP	AG16.00 (15.00, 16.00,17.00)	1180	498	31	523	3701	163	A8	WITHOUT HLV	3.20	8045	6825	5800	5460	5120	4390	
										46	17735	15045	12785	12035	11290	9680	
		46.5	19.6	39	20.6	145.7	151	-	-	WITH HLV	3.20	8110	4830	4105	3865	3625	3105
											46	17880	10650	9050	8520	7990	6845
500/60-22.5 IMP	AG16.00 (15.00, 16.00,17.00)	1180	498	31	523	3701	-	-	WITH HLV	4.20	9655	8190	6960	6550	6145	5265	
										61	21285	18055	15345	14440	13545	11605	
		46.5	19.6	39	20.6	145.7	-	-	-	-	4.20	10110	6905	5870	5525	5180	4440
											61	22290	15225	12940	12180	11420	9790

HLV: Duty cycles where one way the vehicle is empty, and the other way the gross vehicle mass exceeds two times the mass of the empty vehicle. May be allowed for a one way distance of maximum 1 km (0.6 miles).

All tires listed are tubeless.

AUTHORIZED DISTRIBUTOR:

camso.co



FORMERLY CAMOPLAST SOLIDEAL