

SOLIDEAL PON 550

BY CAMSO



PRESS-ON
TIRES



DURABILITY YOU CAN RELY ON

Made with high-performance, natural rubber compounds. Resists chunking and cutting in the most demanding applications, while delivering maximum life and stability for medium intensity applications.

camso.co

PERFORMANCE

INTENSITY



ENERGY SAVINGS



TIRE LIFE



**ROAD
FREE
COMPANY**


FORMERLY
CAMOPLAST
SOLIDEAL

PRESS-ON TIRES

SOLIDEAL PON 550

BY CAMSO

TIRE SIZE ⁽¹⁾	ACTUAL TIRE DIMENSIONS				REPLACEMENT OVERALL DIAMETER ⁽⁶⁾ (mm)	LOAD CAPACITY ⁽²⁾ Counterbalanced lift trucks (kg)					
	OVERALL DIAMETER (mm)	OVERALL WIDTH (mm)	ROLLING CIRCUMFERENCE (mm)	STATIC LOADED RADIUS (mm)		10 km/h		16 km/h		25 km/h	
						LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL
10 x 5 x 6 1/2	256	127	798	121	230	1010	830	905	760	735	605
13 1/2 x 5 1/2 x 8	347	140	1078	163	303	1510	1240	1345	1130	1095	895
14 x 4 1/2 x 8	360	114	1118	169	312	1170	960	1045	875	850	695
14 x 5 x 10	358	127	1118	171	328	1335	1095	1195	1000	970	795
15 1/2 x 5 x 10	396	127	1237	187	353	1470	1210	1315	1100	1070	875
16 x 5 x 10 1/2	411	127	1275	193	367	1510	1240	1345	1130	1095	895
16 x 6 x 10 1/2	411	152	1257	192	367	1910	1570	1710	1435	1390	1140
16 x 7 x 10 1/2	411	178	1275	193	367	2325	1910	2070	1740	1685	1380
15 x 5 x 11 1/4	383	127	1197	185	355	1390	1140	1240	1040	1010	830
16 1/4 x 5 x 11 1/4	415	127	1297	196	376	1530	1250	1360	1145	1105	905
16 1/4 x 6 x 11 1/4	415	152	1298	198	376	1920	1580	1715	1440	1395	1140
16 1/4 x 7 x 11 1/4	415	178	1297	197	376	2325	1900	2060	1735	1680	1380
18 x 5 x 12 1/8	462	127	1436	219	415	1640	1350	1470	1230	1195	980
18 x 6 x 12 1/8	462	152	1436	218	415	2100	1720	1870	1575	1525	1250
18 x 7 x 12 1/8	462	178	1436	218	415	2550	2100	2280	1910	1855	1520
18 x 8 x 12 1/8	462	203	1436	217	415	3000	2475	2680	2250	2180	1790
18 x 9 x 12 1/8	462	229	1436	218	415	3450	2850	3090	2600	2510	2060
21 x 6 x 15	538	152	1675	256	490	2350	1930	2100	1765	1710	1400
21 x 7 x 15	538	178	1675	255	490	2875	2350	2560	2150	2085	1710
21 x 8 x 15	538	203	1660	252	490	3375	2775	3025	2540	2455	2015
21 x 9 x 15	538	229	1674	252	490	3900	3200	3475	2920	2830	2320
20 x 8 x 16	510	203	1596	247	480	3010	2470	2685	2255	2185	1790
22 x 6 x 16	563	152	1756	268	516	2450	2000	2180	1830	1770	1450
22 x 7 x 16	563	178	1756	267	516	2975	2450	2650	2230	2160	1770
22 x 8 x 16	563	203	1756	267	516	3500	2875	3130	2625	2545	2085
22 x 9 x 16	563	229	1756	267	516	4050	3325	3600	3025	2930	2400
22 x 10 x 16	563	254	1835	276	516	4575	3750	4080	3425	3315	2720
22 x 12 x 16	564	305	1756	268	517	5625	4625	5030	4225	4090	3350
28 x 10 x 22	716	254	2324	345	669	5470	4490	4880	4100	3970	3255
28 x 12 x 22	716	305	2234	344	669	6740	5540	6020	5060	4900	4015



**HIGH-PERFORMANCE
NATURAL RUBBER COMPOUND**

- Reduces chunking and cutting
- Suitable for both IC and electric trucks



**WIDE PROFILE AND FLAT
FOOTPRINT**

- Increases stability and grip

HUGE LUG DEPTH

- Increases life and traction

AUTHORIZED DISTRIBUTOR:

Remarks

- (1) Tolerances on wheel diameter • Code designated sizes (in): nominal rim diameter +0.005"/-0" • Metric sizes (mm): h11 according to ISO/R286. Surface roughness Ra < 6.3 μm • Chamfer 5 mm wide @ 30°
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted.
- (3) The tire is considered worn out when the outside diameter is equal or smaller than the replacement overall diameter.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.



Camso is the best of Camoplast and Solideal.
To keep moving forward while staying true to our history,
we're now the Road Free company.

camsoco.com



FORMERLY
CAMOPLAST
SOLIDEAL