

CPCD 10-35-R

Diesel Forklift

1.0/1.5/1.8/2.0/2.5/3.0/3.5T



Distinguishing Mark

Model Designation (T)	CPCD10-R	CPCD15-R	CPCD18-R
Rated Capacity (T)	1000kg	1500kg	1700kg
Operator Type (T)	seated	seated	seated
Lift Height (T)	3000mm	3000mm	3000mm
Wheelbase (T)	1400mm	1400mm	1400mm
Travel Speed, Rated/variable (T)	~14.3 km/h	~14.3 km/h	~14.3 km/h
Turning Radius (T)	1225mm	1170mm	1001mm
Service Weight (T)	2400kg	2740kg	2850kg
Fork dimensions(LxR) (T)	25x100x620mm	25x100x620mm	25x100x620mm
Power type (T)	Diesel	Diesel	Diesel

What do you want?

Reliability

Efficiency

Durability

Safety

REDDOT provide professional solution

Turning radius and width of right angle stacking aisle are decreased through reducing the dimensions of whole truck that raise the efficiency of storhouse.

The environment-friendly engines all meet related emission control regulation. The noise emission also comes up to EU standard.



The forklifts all adopt the new type drum brake, water-proof slot on the brake drum and framework oil seal on the axle tube avoid water or oil entering the brake drum, enable the dependability of brake to raise, consumedly.

Details show



The clearance between the steering axle and support rod can be adjusted, to improve the adaptability for ground.



Adopted advanced ergonomic technology optimizes the design of control system, improves the comfortable of operation much more.



The extra foot space is provided to reduce operator fatigue as significantly. The new wide-open, non-slip step makes getting in and out easy and safe.



The high performance specific tires for forklift trucks increase the work life of tires much more.



Compact design offers same dimensions as conventional integrated models. May be coupled to the differential axles. Making installation, removal, and maintenance easy.



In addition to the soft landing system, the soft lifting system is adopted (front lifting cylinders of triplex mast and full free duplex mast), as a result, the noise and shock of the mast significantly decreases.

Option

Options

- 2.2/3.0/4.0/5.0/6.0/8.0/10.0/12.0/15.0/18.0/20.0/22.0/25.0/30.0/35.0/40.0/45.0/50.0/55.0/60.0/65.0/70.0/75.0/80.0/85.0/90.0/95.0/100.0/105.0/110.0/115.0/120.0/125.0/130.0/135.0/140.0/145.0/150.0/155.0/160.0/165.0/170.0/175.0/180.0/185.0/190.0/195.0/200.0/205.0/210.0/215.0/220.0/225.0/230.0/235.0/240.0/245.0/250.0/255.0/260.0/265.0/270.0/275.0/280.0/285.0/290.0/295.0/300.0/305.0/310.0/315.0/320.0/325.0/330.0/335.0/340.0/345.0/350.0/355.0/360.0/365.0/370.0/375.0/380.0/385.0/390.0/395.0/400.0/405.0/410.0/415.0/420.0/425.0/430.0/435.0/440.0/445.0/450.0/455.0/460.0/465.0/470.0/475.0/480.0/485.0/490.0/495.0/500.0/505.0/510.0/515.0/520.0/525.0/530.0/535.0/540.0/545.0/550.0/555.0/560.0/565.0/570.0/575.0/580.0/585.0/590.0/595.0/600.0/605.0/610.0/615.0/620.0/625.0/630.0/635.0/640.0/645.0/650.0/655.0/660.0/665.0/670.0/675.0/680.0/685.0/690.0/695.0/700.0/705.0/710.0/715.0/720.0/725.0/730.0/735.0/740.0/745.0/750.0/755.0/760.0/765.0/770.0/775.0/780.0/785.0/790.0/795.0/800.0/805.0/810.0/815.0/820.0/825.0/830.0/835.0/840.0/845.0/850.0/855.0/860.0/865.0/870.0/875.0/880.0/885.0/890.0/895.0/900.0/905.0/910.0/915.0/920.0/925.0/930.0/935.0/940.0/945.0/950.0/955.0/960.0/965.0/970.0/975.0/980.0/985.0/990.0/995.0/1000.0



Application



Factory



Warehouse



Outdoor work

CONFIDENT CHOICE IN
CARGO HANDLING

THE TRUST OF THE CUSTOMER IS OUR GREATEST RECOGNITION

CONTACT US TO GET AN OFFER