

# CPC(Q/Y)D10-35-XF

Diesel/Gasoline/LPG/DUAL FUEL Forklift  
1.0/1.5/1.8/2.0/2.5/3.0/3.5T



Model	CPCD/CPQD 18	CPCD/CPYD/CPQD/CPQYD 15	CPCD/CPYD/CPQD/CPQYD 18
Rated Capacity (t)	1.8T	1.5T	1.8T
Operator Type (t)	seated	seated	seated
Wheelbase (mm)	3000mm	3000mm	3000mm
Overall Height (mm)	1475mm	1475mm	1475mm
Travel Speed, Load/Unload (km/h)	~17.5-18.4	~17.2-18.4	~17.2-19.6
Turning Radius (mm)	1965mm	1965mm	2015mm
Service Weight (kg)	2510kg	2650kg	2700kg
Fork dimensions (LxW) (mm)	45x100x220	45x100x220	50x100x220
Power Type (t)	Diesel/Gasoline	Diesel/LPG/Gasoline/DUAL FUEL	Diesel/LPG/Gasoline/DUAL FUEL

  

Model	CPCD/CPYD/CPQD/CPQYD 20	CPCD/CPYD/CPQD/CPQYD 25	CPCD/CPYD/CPQD/CPQYD 30	CPCD/CPYD/CPQD/CPQYD 35
Rated Capacity (t)	2.0T	2.5T	3.0T	3.5T
Operator Type (t)	seated	seated	seated	seated
Wheelbase (mm)	3000mm	3000mm	3000mm	3000mm
Overall Height (mm)	1450mm	1450mm	1700mm	1700mm
Travel Speed, Load/Unload (km/h)	~17.5-18.4	~17.5-18.7	~17.2-18.4	~17.2-19.6
Turning Radius (mm)	2100mm	2245mm	2515mm	2415mm
Service Weight (kg)	3405kg	3705kg	4350kg	4785kg
Fork dimensions (LxW) (mm)	40x122x1070	40x122x1070	45x122x1070	50x122x1070
Power Type (t)	Diesel/LPG/Gasoline/DUAL FUEL	Diesel/LPG/Gasoline/DUAL FUEL	Diesel/LPG/Gasoline/DUAL FUEL	Diesel/LPG/Gasoline/DUAL FUEL

## What do you want?

Reliability Efficiency Durability Safety

## REDDOT provide professional solution

The double lifting cylinders provide better forward

Dynamic load sensing hydraulic steering system, Efficiency lighting system, lower fuel consumption combine to provide increased productivity and reduced operating costs.



By optimizing transmission design, the power train provides higher efficiency. The fuel consumption is reduced by 10%.

Optimal visibility in all directions create the best conditions for high productivity through relaxed and safe working.

### Details show



The new aluminum alloy transmission with full floating structure features excellent heat dissipation capability, more and thicker disc meet the most demanding applications.



The new stamped air cleaner featuring tangential intake, double seal with safety filter is durable, corrosion-free and vibration-resistant, provides better filter efficiency and lower intake resistance than the previous.



Extra capacity combined radiator with serpentine wave and optimized heat dissipation channel enhance the heat dissipation capability to keep engine reliability even in heavy-duty applications.



The new vehicle controller integrates all electrical components, features excellent durability for temperature, water and vibration for most demanding operation.



XF series features rugged design, stamped frame and engine hood, stamped instrument panel and head guard, heavy profile rail mast combine to provide excellent rigidity, which ensures outstanding reliability even in heavy-duty work.



Optimized hydraulic breather structure and integrated with return oil filter can prolong the service life of hydraulic pressure system.

### Option



### Application



Factory



Warehouse



Indoor work

CONFIDENT CHOICE IN  
CARGO HANDLING

THE TRUST OF THE CUSTOMER IS OUR GREATEST RECOGNITION

CONTACT US TO GET AN OFFER