

CPD10-35-A

Electric Forklift

1.0/1.5/1.8/2.0/2.5/3.0/3.5T



Configuration Model	CPD10-A	CPD15-A	CPD18-A	CPD20-A
Rated Capacity	1.0T	1.5T	1.8T	2.0T
Operator Type	seated	seated	seated	seated
Lift Height	3000mm	3000mm	3000mm	3000mm
Wheel base	1300mm	1300mm	1300mm	1435mm
Travel Speed, Laden/Unladen	14/18 km/h	14/18 km/h	13.5/18 km/h	14/18 km/h
Turning Radius	1900mm	1900mm	1900mm	2050mm
Service weight	2880kg	2940kg	3090kg	3880kg
Fork dimensions(LxW/T)	25x120x920mm	25x120x920mm	25x120x920mm	40x122x1070mm
Power type	Diesel	Diesel	Diesel	Diesel

Model Description	CPD25-A	CPD30-A	CPD35-A
Rated Capacity	2.5T	3.0T	3.5T
Operator Type	seated	seated	seated
Lift Height	3000mm	3000mm	3000mm
Wheel base	1435/1625mm	1625mm	1625mm
Travel Speed, Laden/Unladen	14/18km/h	14/18km/h	12/13km/h
Turning Radius	2090/2250mm	2250mm	2510mm
Service weight	4160/4380kg	4050kg	5500kg
Fork dimensions(LxW/T)	40x122x1070mm	45x125x1070mm	50x125x1070mm
Power type	Diesel	Diesel	Diesel

What do you want?

Reliability

Efficiency

Durability

Safety

REDDOT provide professional solution

Battery cover with auto lock spring for easy battery service and replacing, and clean the oil tank

Side battery charging solution is applied for heavy and long time application ground.

Easy opened counterweight cover is to protect the internal controllers to avoid water and dust

Big dimension anti-slide rubber pad



Details show



The new designed steering wheel / new brake system and the easy-to-operate levers provide total handling operation.



In addition to the soft landing system, the soft lifting system is adopted (front lifting cylinders of triplex mast and full free dup-lex mast), as a result, the noise and shock of the mast significantly decreases.



New designed wide view mast provides better forward view ability.



The extra foot space is provided to reduce operator fatigue significantly. The new wide-open, non-slip step makes getting in and out easy and safe.



Imported high performance, and new generation AC controller



Advanced parallel layout of drive motor and lower located battery up to chassis bottom provide good stability to the truck.

Option



Application



Factory



Warehouse



Indoor work

CONFIDENT CHOICE IN CARGO HANDLING

THE TRUST OF THE CUSTOMER IS OUR GREATEST RECOGNITION

CONTACT US TO GET AN OFFER