

# CPD13-20TV8

Three-wheel Electric Forklift 1.3/1.5/1.6/1.8/2.0T



Distinguishing Mark	CPD13TV8	CPD15TV8	CPD16TV8	CPD18TV8	CPD20TV8
Rated Capacity	1.3t	1.5t	1.6t	1.8t	2.0t
Operator Type	seated	seated	seated	seated	seated
Lift Height	3000mm	3000mm	3000mm	3000mm	3000mm
Fork Dimensions	40x100x920(mm)	40x100x920(mm)	40x100x920(mm)	40x100x920(mm)	40x100x920(mm)
Travel Speed, Load/unload	13/14 km/h	13/14 km/h	13/14 km/h	13/14 km/h	13/14 km/h
Turning Radius	1.07m	1.07m	1.07m	1.07m	1.07m
Service weight(include battery)	3000kg	3050kg	3140kg	3140kg	3400kg
Type of Drive Unit	AC	AC	AC	AC	AC
Battery Voltage/Nominal Capacity	48/400	48/400	48/500	48/500	48/500

## What do you want?

Reliability

Efficiency

Durability

Safety

## REDDOT provide professional solution

Ergonomics Design

External full steel cover

International Quality Components

Long time durability ensure shifts works/heavy duty working.



### Details show



High quality components, ZAPI controller, Germany SCHABMULLER driving motor, USA KDS motor, ZAPI display, Germany interque brake.



Fault code through the digital display.



Strong safety guard, ensure safety operations.



Wide view mast, two stage & three stage are available. Side view also good. Ensure safety operations.



Big operation space ensure comfortably.



Reliable structure humanity design to reduce the truck maintenance.

### Option



### Application



Factory



Warehouse



Indoor work

CONFIDENT CHOICE IN  
CARGO HANDLING

THE TRUST OF THE CUSTOMER IS OUR GREATEST RECOGNITION

CONTACT US TO GET AN OFFER